ARMOIRE HUMIDE DE CONSERVATION
REF E0138-01-A001

Armoire humide à ruissellement pour la conservation des moules mortiers prismatiques selon la norme EN 196-1.

Caractéristiques générales :

- Fabrication en aluminium et polycarbonate
- Conservation dans l'air humide jusqu'à de 16 moules disposés sur 4 étagères
- Humidité générée par pulvérisation de l'eau par ruissellement sur la paroi arrière
- Affichage de la température par régulateur électronique de précision.
- Maintien de température à 20 +/- 1°C par résistance chauffante interne et groupe thermostaté secondaire externe réglable en température
- Circulation de l'eau par pompe externe assurant le ruissellement interne
- Dimensions intérieures 109x47x120 cm.
- Dimensions extérieures 137x54x149 mm.

Armoire humide
- Alimentation Monophasée 230V, 50 Hz, 2000 W.
- Poids 100 kg

Groupe thermostaté
- Alimentation Monophasée 230V, 50 Hz, 400 W.
- Poids 20 kg

Remarques

- Afin d'homogénéiser et stabiliser la température interne dans l'armoire humide il est fortement conseillé de placer cet équipement dans une salle climatisée à 20°C

WET STORAGE CABINET

REF E0138-01-A001

Wet runoff cabinet for the preservation of prismatic mortar moulds.

Technical features:

- Aluminium and polycarbonate manufacturing
- Preservation in moist air up to 16 mussels on 4 shelves
- Moisture generated by spraying water by runoff on the back wall
- Temperature display by precision electronic regulator.
- Temperature maintenance at 20 degrees Celsius by internal heating resistance and thermostatized group
- temperature-adjustable external secondary
- External water circulation for internal runoff
- Interior dimensions 109x47x120 cm.
- Exterior dimensions 137x54x149 mm.
- Wet cabinet
- Monophased Power 230V, 50 Hz, 2000 W.
- Weight 100 kg
- Thermostated Group
- Monophased power 230V, 50 Hz, 400 W.
- Weight 20 kg

Note:

To homogenize and stabilize the internal temperature in the wet cabinet it is strongly advised to place this equipment in an air-conditioned room at 20°C